

Product Specification

50 Ohm In-Conduit Cable, 1/2"

Copper Outer Conductor - ACC012J50



Description	Product Number
Standard Cable	
1/2", Corrugated, Copper Outer Conductor, Black Polyethylene Jacket	ACC012J50
Physical Dimensions	
Center Diameter, in (mm)	0.188 (4.78)
Diameter Over Outer Conductor, in (mm)	0.550 (13.97)
Maximum Diameter Over Jacket, in (mm)	0.63 (16.00)
Center Conductor	Copper-Clad Aluminum
Outer Conductor	Corrugated Copper
Jacket Color	Black
Electrical Characteristics	
Maximum Frequency, GHz	10
Peak Power Rating, KW	40
DC Resistance, Ohms/1,000 ft (1,000 m)	
Center	0.46 (1.51)
Outer	0.39 (1.28)
DC Breakdown, kV	2
Capacitance, pF/ft (m)	22 (72.12)
Inductance, mH/ft (m)	0.057 (0.187)
Jacket Spark, kV RMS	8
VSWR min, (dB)	1.25 (19.0)
VSWR typical, 700-960 / 1700-2200 MHz (dB)	1.13 (24.3)
Impedance, Ohms	50 ± 2
Velocity of Propagation	94%
Mechanical Characteristics	
Minimum Bend Radius, in (mm) - Single	2 (50.8)
Minimum Bend Radius, in (mm) - Multiple	5 (127)
Cable Weight, lb/ft (kg/m)	0.18 (0.27)
Bending Moment, ft lb (N m)	3.0 (4.1)
Tensile Strength, lb (kg)	275 (125)
Flat Plate Crush, lb/in (kg/mm)	110 (2.0)
Number of Bends, minimum	15
Recommended Install Temp., °F (°C)	+5° to 194° (-15° to 90°)
Recommended Storage Temp., °F (°C)	+5° to 194° (-15° to 90°)
Recommended Operating Temp., °F (°C)	+5° to 194° (-15° to 90°)
Standard Conditions	
For Attenuation: VSWR 1.0, Ambient Temperature 20°C (68°F)	
For Average Power: VSWR 1.0, Ambient Temperature 40°C (104°F), Inner Conductor Temperature 100°C (212°F), No Solar Loading	
Regulatory Compliance/Certifications	
RoHS 2011/65/EU Compliant	
TL 9000 H-V - All Cables designed and manufactured under this quality management system	

Frequency, MHz	Attenuation		Average Power kW
	dB/100 ft	dB/100 m	
100	0.65	2.13	4.82
450	1.43	4.69	2.21
500	1.52	4.99	2.10
600	1.64	5.38	1.91
700	1.75	5.74	1.76
800	1.87	6.14	1.68
900	1.98	6.50	1.55
960	2.04	6.69	1.49
1000	2.10	6.89	1.46
1500	2.62	8.60	1.18
1700	2.79	9.15	1.10
1800	2.88	9.45	1.07
1950	3.01	9.88	1.02
2000	3.05	10.01	1.01
2100	3.14	10.30	0.99
2200	3.23	10.60	0.96
2300	3.33	10.93	0.94
2400	3.42	11.22	0.91
2500	3.48	11.42	0.90
2700	3.65	11.97	0.86
3000	3.83	12.57	0.81
3300	4.02	13.19	0.76
3400	4.08	13.39	0.66
4000	4.45	14.60	0.69
4900	5.00	16.40	0.60
5000	5.06	16.60	0.60
5200	5.34	17.52	0.58
5300	5.48	17.98	0.57
5600	5.90	19.36	0.53
5825	6.32	20.73	0.49

Trilogy AirCell® Cable

Proud to be 100% Made in the USA

